



AKURATE
DYNAMICS

X-23

PROPORTIONER

- COMPACT AND STREAMLINED DESIGN
- PERFECT FOR LOW TO MEDIUM VOLUME WALL FOAM APPLICATIONS
- ACE CONFORMANCE REPORTING VALIDATES JOB SPECS
- RIG CONNECT ENABLED FOR REAL-TIME SUPPORT

X-23 PROPORTIONER

All of the proportioner technology you've come to expect from Akurate Dynamics in a compact design



- Individual gear pump driven system with integrated software to independently adjust motor speeds
- High resolution flow meters analyze thousands of data points to create seamless adjustments to chemical flow
- Intuitive system dynamically adjusts to automatically ensures on-ratio application everytime
- Compact and space-saving. Perfect for smaller rigs

SPECIFICATIONS

APPLICATION	Low to medium wall foam applications
POWER INPUT	Nominal 200-240 VAC, 1 Phase or 3 Phase, 50/60 HZ
WEIGHT	500 lbs
DIMENSIONS	36" (Width) X 28" (depth) X 52" (Height)
OPERATING TEMP	50 - 130 Degrees Fahrenheit
MAX FLUID WORKING PRESSURE	2200 PSI
MAX FLUID TEMP	150 Degrees Fahrenheit
POWER BUDGET ELECTRIC HEAT	8.0 KW
HMI	TFT - LCD with Touch Screen
HOSE ELECTRICAL CODE	GFI Protected Hoses
MAX HOSE LENGTH	300'
ALARMS	Descriptive Alarms with Time Stamp